

(12) INTERNATIONAL PUBLICATION PUBLISHED IN PURSUANCE OF THE
PATENT COOPERATION TREATY (PCT)

(19) World Organization of Intellectual Property International Bureau [WIPO] (10) International Publication No.:
PCT **WO 2004/030170 A2**

(43) International publication
date: April 8, 2004
(4/8/2004)

(51) International patent classification⁷: H 02 B 1/044

(21) International application number: PCT/FR2003/050050

(22) International filing date: September 11, 2003 (9/11/2003)

(25) Filing language: French

(26) Publication language: French

(30) Data relative to priority:
02 11807 September 24, 2002 (9/24/2002) FR

(71) Applicant: *(for all designated states except US)*: FCI
[FR/FR]; 145 rue Yves Le Coz, F-78000 VERSAILLES (FR)

(72) Inventors; and

(75) Inventors/Applicants *(only for US)*: BISSON, Didier [FR/FR]; 28, rue des
Oréades, F-25300 DOUBS (FR). CHANTREL, Philippe [FR/FR]; 13, rue
Arago, F-25300 PONTARLIER (FR). MOUGIN, Franck [FR/FR]; 12, rue
des Charmilles, F-25300 DOMMARTIN (FR).

(74) Agent: SCHMIT, Christian, Norbert,; SCHMIT CHRETIEN SCHIHIN, 8
place du Ponceau, F-95000 CERGY (FR).

(81) Designated states *(national)*: CN, US

(84) Designated states *(regional)*: European Patent (AT, BE, BG, CH, CY, CZ,
DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR).

Published:

-- without International Search Report, will be published again when this report is received.

With regard to the two-letter country codes and other abbreviations, refer to the "Explanatory notes relating to codes and abbreviations" at the beginning of each regular issue of the PCT Gazette.

(54) Title: BUS BAR FASTENING AND CONTACT DEVICE

(57) Abstract:

Fastening and contact device (1) to be mounted on a plate (2) provided with bus bars, said device comprising a sleeve (5) and a ring (6) to be mounted through an opening (3) of the plate. The sleeve comprises shoulders (7) that come to rest on a first side (4) of the plate, while the ring slides along the sleeve until it comes into contact with a second side (10) of the plate. The plate is clamped between the sleeve and the ring when a tightening means (13) cooperates with the sleeve and a complementary device (14) to which the plate is connected.

